

Type A

**Application:**

- used primarily on irrigation and suction lines

**Features:**

- hot dipped, galvanized
- has a double pin locking lever for smooth closing action
- Type A Agri-Lock style locks on female style
- Each coupler is equipped with a safety pin to prevent accidental openings.
- *These fittings are not recommended for chemicals or any hazardous type materials where the possibility of leakage would result in health or environmental concerns. Consult Dixon® for recommendations.*



**Female with Hose Shank**

**Feature:**

- supplied with gasket

Size	Galvanized Steel Part #
10"	<b>FC21210</b>
12"	<b>FC21212</b> <sup>1</sup>

<sup>1</sup> 12" supplied with M20412 lever assist bar found on page 256



10"

**Female with Machined Hose Shank**

**Features:**

- Dixon® combination nipple style hose shank machined from Schedule 40 pipe
- recommended for use with steel King Crimp™ sleeves
- supplied with gasket

Size	Galvanized Steel Part #
10"	<b>FC21210ST100</b>
12"	<b>FC21212ST120</b> <sup>1</sup>

<sup>1</sup> 12" supplied with M20412 lever assist bar found on page 256



12"

**Female with 150# ASA Flange**

**Feature:**

- supplied with gasket

Size	Galvanized Steel Part #
10"	<b>FC22310</b>
12"	<b>FC22312</b> <sup>1</sup>

<sup>1</sup> 12" supplied with M20412 lever assist bar found on page 256

- For flange dimensions, diagrams and additional information please reference [dixonvalve.com](http://dixonvalve.com).



12"